

Carry-me Owner's Manual

Q.1 What's in the Box?

- In the shipping box is a complete Carry-me folded up. Before you start to unfold it and make it ready to ride, make yourself familiar with all its parts and components.



- Open the seat clamp and raise the seat up about 6 inches, turn it to face the front and close the clamp fully.
- Swing the seat tube down and push down the seat stay lock to fix the seat stay in position.
- Open the clamp on the head tube, swing the head tube up and lock the clamp fully.



- Unfold the pedals.
- Align and adjust heights of handlebar and seat for proper fit for riding.

Note:

- Carry-me has kickstand. It can either stand on the kickstand or on the rear carrier.



Q.2 How to Make Carry-me Ready to Ride?



- Join the two ends of the handlebars to the center piece. Push down the bronze bottom, insert it to the center piece and close the clamp fully.
- Open the clamp on top of the stem and raise it up about 6 inches. Turn the stem counter-clockwise to face front and close the clamp fully.

Q.3 How to Fold the Bicycle?



- To fold in the front end: Hold the handlebar with one hand, open the clamp at the bottom of the head tube with the other hand, swing the head tube downward to the main frame, and stand the bicycle up on the rear carrier.
- To fold in the rear end: Open the seat post clamp, rotate the seat to face back and close the seat clamp again. Open the seat-stay lock and swing the seat tube toward the main frame.

Q.4 How to Reduce the Bicycle Height?



- Open the seat clamp, push down the seat and close the seat clamp again.
- Open the clamp at the top of the handlebar stem, rotate the handlebar clockwise and push it down till it touches the seat. Close the clamp again.

Q.5 How to Reduce the Bicycle Width?



- Open the handlebar clamps, push down the bronze bottoms, and then pull out the handlebars to separate them from the center section.
- Fold the pedals: Push the pedals inward and fold them down.

⚠ Important Safety Checklist!

- Check and make sure that all clamps are properly tightened.
 - 1) The handlebars should be tight with no play.
 - 2) The head tube clamp should be fully tightened not allowing rotation or play.
 - 3) The seat stay clamp should be fully tightened.
 - 4) The seat post clamp should be fully tightened not allowing any rotation or sliding.
- Do not raise the handlebar stem and seat post up beyond the maximum insertion mark.
- Always wear a helmet and abide by all traffic regulations and courtesies!
- Rear carrier max. loading: 10kg / Average speed: 13km/h
Max. height: 145-185cm / Max. loading: 80kg

⚠ Important Maintenance Checklist!

- 1st service inspection after at most 300 km or at latest one months after purchase, repeat every 3 months.
- Parts need lubrication: chain, headset, bearings.
- Parts prohibit lubrication: seatpost, seat tube, adjustable stem, rims.
- Repeat lubrication every half month or after at most 150 km ride.
- Apply lubrication immediately after washing or riding in rainy day.



236 Hsia Chuan Tze, Yung An, Hsin Wu, Taoyuan, Taiwan, ROC
 Tel: +886-3-4861231 Fax: +886-3-4861215
 Web: <http://www.pacific-cycles.com>
 Email: team@pacific-cycles.com